



BURSTING DISCS

Reverse Acting - Type Axis®

Description

The Axis® is a reverse acting, 95% operating ratio bursting disc, utilizing Fike's innovative G2® design and manufacturing technology.

The Axis® bursting disc has a "line of weakness" on the dome of the disc instead of a score line. There are no stress zones and no tool marks or indentations on the process side of the disc, making this a disc with a completely smooth process surface without induced stress zones.



Burst / Performance Tolerance

Range (barg)	Tolerance (barg)
0.48-1.02	± 0.07
1.03-2.76	± 0.14
> 2.76	± 5%

Features and Benefits

- 95% operating ratio
- Superior cycling conditions
- Superior corrosion resistant material selection
- Suitable for all process media - liquid, gas, 2-phase
- Ideal for PRV / SRV isolation and in-situ testing, will allow a backpressure of 1,25 times the specified pressure
- Can be used in double disc configurations

Specifications

Type of disc	Axis®																		
Action	Reverse acting																		
Available size range	DN25-DN300 / 1"-12"																		
Disc material	1.4401 / 1.4404 (316/316L SST)									Hastelloy C276									
Maximum Temperature	482°C																		
Burst Pressure (barg)	DN	25	40	50	80	100	150	200	250	300	25	40	50	80	100	150	200	250	300
	Inch	1 ⁽¹⁾	1.5	2	3	4	6	8	10	12	1 ⁽²⁾	1.5	2	3	4	6	8	10	12
	MIN	0.69	0.55	0.55	0.48	0.48	0.55	0.55	0.55	0.55	0.83	0.55	0.48	0.55	0.48	0.48	0.55	0.55	0.55
MAX	36.20	26.54	26.54	22.41	19.66	13.79	10.34	6.89	4.83	41.37	26.54 ⁽¹⁾	32.41	29.65	20.69	13.79	9.65	6.21	4.14	
Ratio of Operating Pressure to Minimum Burst Pressure	95%																		
Protective coating ⁽³⁾	Yes																		
Cyclic duty	R																		
Pulsating duty	R																		
Full Vacuum	R																		
Polymerisation Process	Yes																		
Hydraulic Service ⁽¹⁾	R																		
Non-fragmenting disc	R																		
Seat configuration	XL/XLO-Flat																		
O-ring seal for reduced fugitive emission	Viton (optional)																		
Use in flanged holders	Yes																		
Use in flanged pretorqueable holders	Yes																		
Use in Union Type holders	No																		
Use in Screw type holders	No																		

R= RECOMMENDED NR= NOT RECOMMENDED

- (1) DN25 / 1" size not suitable for use in liquid service with burst pressure less than 4.48 barg and inlet pipe length > 250 mm.
 (2) Maximum burst pressure with 1.4401 / 1.4404 (316/316L SST) ring. 13.79 barg is the maximum burst pressure rating with a Hastelloy C276 ring.
 (3) For applications needing extra corrosion protection the Axis® bursting disc can be ordered with an optional FEP or PFA fluoropolymer liner on the process side. For FEP liner: minimum burst pressure 2 barg, maximum temperature 204°C. For PFA liner: minimum burst pressure 3.1 barg, maximum temperature 260°C.

Performance Attributes				Process Media		Bursting Disc Holders	
Operating Ratio	Non-fragmenting	Vacuum resistance	Pulsating/Cycling	Liquid	Vapour/gas	Bolted Type	Pretorqueable
95%	Yes	Yes	Yes	Yes ⁽¹⁾	Yes	Yes	Yes

- (1) Consult Fike for liquid full, hydraulic applications.
 Consult Fike for applications where viscous liquid is against the disc at the time of disc opening.

U.S. Patents 7,600,527 and 6,945,420 and Foreign Patents. U.S. and Foreign Patents Pending.



CORONA SERWIS Sp. z o.o.
 ul. Baidona 16/27, 40-115 Katowice
 tel. +48 32 255 53 53, fax +48 32 720 20 88
 NIP 634-283-12-56

8.1265.00.9

All above data are subject to change without notice. They must not be used unless confirmed in writing.

Fike Europe B.v.b.a. · Toekomstlaan 52 · B2200 Herentals · Belgium
 Tel. +32 (0)14 210031 · Fax +32 (0)14 210743 · email: fike-europe@fike.com · website: http://www.fike.be

Fike United Kingdom · Maidstone · Kent · ME14 1 PF
 Tel. +44 (0) 1622 677081 · Fax +44 (0) 1622 685737 · email: sales@fike.co.uk · website: http://www.fike.co.uk

Fike Ireland · Redhousehill · Patrickswell · Co. Limerick
 Tel. +353 (0)61 215555 · email: sales@fike.ie · website: http://www.fike.ie

